

HERDER®

Frontier MBK 110



The **Frontier MBK 110**, in left or right hand version.

The “Handyman” with 110 degrees slewing system to the front and electric single-joystick control for optimal verge and bank maintenance.

Comfort and safety with electric float systems and hydraulic front axle lock.

Fully equipped with a tool box, oil cooler and max. hydraulic output of 50 kW.

Maximum flexibility through multifunctional hydraulic system and low total weight.

Sustainability due to acceptable price/durability and the possibility to use 60 kW tractors and up.



Swineshead Road (A52)
Wyberton Fen, Boston, Lincs. Pe21 7JG.
Tel: 01205 311313 Fax : 01205 30016
E-mail: info@mastenbroek.com
www.mastenbroek-environmental.com



Machine factory HERDER B.V.
the Netherlands
Tel: +31(0)118-679500
E-mail: sales@herder.nl
www.herder.nl

Technical Specifications HERDER® Frontier MBK 110

Can be used on tractors from 60 kW.

Technical details:

Working reach with mowing bucket measured from the slewing column: 490 cm.

- Pump capacity at 540 RPM at the PTO-shaft:
 - Attachments pump: 90 l/min.;
 - Position 1 (mowing bucket): stepless 0-40 l/min - 150 bar
 - Position 2 (flailmower): 90 l/min - 330 bar;
- Pump floating position: 14 l/min;
- Pump control valve: 60 l/min;
- Operating pressure control valve: 200 bar max.
- Tank capacity hydraulic oil: 200 litres.
- Slew reach 110° to the front.
- Oil cooler (9,5 kW)
- Tool box.
- Electric single-handle control.
- Electrically operated front axle lock.
- Electrically adjustable floating position.
- Switchable free travel position on the bucket cylinder.
- The machine can be dismantled in about 30 min.



Optional equipment at extra cost:

- Disconnecting construction for easy (dis-)mounting.
- Supporting leg or wheel, controlled via tractor hydraulics.
- Conveyor belt function via tractor hydraulics with motor spool.
- Attachment swivel with safety valve via tractor hydraulics.
- Quick connecting system for easy change of attachments.
- Left-hand fitting.
- 1000 RPM gear box.
- Long working reach 560 cm.

